

ECOSYS M5526cdn/A & ECOSYS M5526cdw/A: Professional Colour Multi-talent

The new 3-in-1 colour device of the legendary ECOSYS models combines the best colour quality and technology making it a perfect fit for your desktop requirements. With its dual-scan document processor, the 4.3 inch touch screen for intuitive use, and program keys to simplify complex workflows improve productivity and qualify this device as an absolute all-rounder. Furthermore, this device contains a long-yield toner with a capacity of up to 3,000 pages in colour – offering low costs per page. Rest assured, it is the perfect multifunctional partner for your business and will offer you a future of brilliant colours.



GENERAL

Technology: KYOCERA ECOSYS, Colour Laser Control panel display: 10,9 cm (4,3 inch) full colour touch panel display

Engine speed: Up to 26 pages A4 per minute in colour and $\ensuremath{\mathsf{b/w}}$

Resolution: 1,200 x1,200 dpi print at reduced speed, multibit technology for print quality of up to 9,600 x 600 dpi (print), 600 x 600 dpi, 256 greyscales per colour (scan/copy)

Recommended Print Volume': 2,800 pages per month Maximum Print Volume': 50,000 pages per month Maximum Life': 100,000 pages or 5 years

Scan Volume1: max. 2,000 pages per month

Warm-up time: Approx. 29 seconds or less

Time to first print: Approx. 9.5/10.5 seconds or less in b/w/colour

Time to first copy: Approx. 8/10 seconds or less in b/w/colour

CPU: 800MHZ

Memory: Standard 512 MB, max. 1,536 MB Standard interface:

ECOSYS MA5526cdn/A: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT) Slot for optional SD/SDHC-Card ECOSYS MA5526cdw/A: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet 10BaseT/100BaseTX/1000BaseT), Wireless LAN, Slot for optional SD/SDHC-Card **Dimensions (W x D x H):** Main unit: 417 x 429 x 495 mm

Weight: Main unit: Approx. 26 kg

Power source: AC 220 ~ 240 V, 50/60 Hz Power consumption:

Power consumption:

Copy/Print: 375 W Ready mode: 41 W

Sleep mode: 1 W

Noise (Sound pressure level: ISO 7779/ISO 9296): Copy/Print BW/colour: 49/49 dB(A) LpA

Ready/Standby mode: 30 dB(A) LpA

Sleep mode: Immeasurably low

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm, Please use paper recommended by KYOCERA under normal environmental conditions. **Input capacity:** 50-sheet multi-purpose tray; 60-220 g/m² A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm-216 x 356 mm) 250-sheet universal casselte: 60-163 g/ m² A4, A5, 46, B5, B6, Letter, Legal, Custom (105 x 148 - 216 x 356mm). Max. Input capacity with options: 550 sheets **Duplex functionality as standard:** Double-sided printing: 60 -120 g/m²; A4, A5, B5, Letter, Legal

Dual scan document processor: 50-sheet, 50-160 g/m2, A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm to 216 x 356 mm)

Output capacity: Max. 150 sheets face-down with paper full detection

PRINT FUNCTIONS

Controller language: PRESCRIBE IIC Emulations: PCL 6 (PCL 5C/PCL-XL), PostScript 3 (KPDL 3), PDF Direct print 1.7. XPS Direct Print Operating systems: All current Windows operating systems, MAC OS X Version 10.8 or higher, Unix, Linux as well as other operating systems on request Fonts/barcodes: 93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PC and other barcodes available as an option)

COPY FUNCTIONS

Max. original size: A4/Legal Continuous copying: 1-999 Zoom range: 25-400 % in 1% steps Preset magnification ratios: 7 Reductions/5 Enlargements Exposure mode: Manual: 9 steps Image adjustments: Text + Photo, Photo, Text, Map, Printed document Features: Auto Colour Mode, Scan-once-copy-many,

electronic sort, 2in1, 4in1, ID-card copy, priority print, program, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail (SMTP), Scan-to-FTP (FTP over SSL), Scan-to-SMB, Scan to USB Host, TWAIN scan (USB, network), WSD (WIA) scan (USB, network) Scan speed: 30 ipm (300 dpi, A4, b/w, simplex), 23 ipm (300 dpi, A4, colour, simplex), 24 ipm (300 dpi, A4, b/w, duplex), 16 ipm (300 dpi, A4, colour, duplex)

Max. scan size: A4, Legal

Original recognition: Text + Photo, Photo, Text, Light Text, Text (for OCR)

Scan file formats: TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS

Compression method: MMR/IPEG

Features: Integrated address book, Active directory support, encrypted data transfer, Blank sheet skip

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19798 Toner-Kit TK-5240K: black toner yield 4,000 pages A4 Starter toner: black toner yield 1,200 pages A4 Toner-Kit TK-5240C, TK-5240M, TK-5230V: cyan, magenta, yellow toner yield 3,000 pages A4

Starter toner: cyan, magenta, yellow toner yield 1,200 pages A4

OPTIONS

PF-5110 Paper feeder: 250 sheets; 60-163 g/m²: A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 mm-216 x 356 mm)

Memory upgrade: MM3-1GB (b): 1,024 MB, MM3-512MB (b): 512MB UG-33: ThinPrint support USB IC Card Reader + Card Authentication Kit (B): Support

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available CB-510-B: Wooden cabinet

MODEL VARIATIONS

ECOSYS M5526cdn/A/KL3: ECOSYS M5526cdn/A incl. warranty extention KYOlife 3 years ECOSYS M5526cdw/A/KL3: ECOSYS M5526cdw/A incl. warranty

extention KYOlife 3 years

WARRANTY

1-year warranty** as standard. KYOCERA guarantees the drum and developer for 3 year or 500,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions. The up to 5-year on-site warranty extension for printer and options.

What's in the box

Main unit, starter toners (black, cyan, magenta, yellow 1,200 pages each, in accordance with ISO/IEC 19798), integrated waste toner box, Product Library DVD, Quick Guide, Safety Guide, Operation panel sheet, label for "Quiet Mode", power supply cord

The device is not designed to achieve the specified volumes in continuous operation. The maximum volumes relate to the use of the print or scan unit and include their use for the printing, copying and scanning functions. Note: In this context, a copied page corresponds to a scanned and a printed page.

Specifications and design are subject to change without notice. TASKalfa, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Mopria is a trademark of Mopria Alliance, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.



KYOCERA Document Solutions Europe B.V. -Bloemlaan 4, 2132 NP Hoofddorp, The Netherlands Tel +31 (0) 20-654-0000 — Fax +31 (0) 20-653-1256



kyoceradocumentsolutions.eu

Kyocera Document Solutions Partner

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. ©2022 KYOCERA Document Solutions Europe B.V.