

Philips Signage Solutions D-Line Display

**43"** UHD (3840 x 2160) 500 cd/m<sup>2</sup>



43BDL4511D

# Say more

# Smart, fast, 24/7 display.

Make it stand out with a fast Philips D-Line Professional 4K UHD display. Philips superb picture quality ensures true colours and intense contrast. You can effortlessly display content from multiple sources on a single screen.

# Brilliant picture. Blazing processor speed.

- Place in landscape or portrait orientation
- 4K UHD. Rich, deep images. Stunning contrast
- · ADS wide-view panel display

# **Operational flexibility**

- Optional OPS Slot
- SmartPower for energy saving

# Cost-effective system solution

- Energy-saving automatic backlight control
- FailOver ensures that content is always playing

# Effortless setup. Total control.

- Operate, monitor and maintain with CMND and Control
- Schedule what you want, when you want with SmartPlayer



# Highlights

# 4K UHD. Rich, deep images

4K UHD. Rich, deep images. Stunning contrast

# ADS wide-view panel display

Be seen from any angle with ADS wide-view technology. Advanced Super Dimension Switch delivers faster on-display picture processing for smoother content transitions, remarkable image accuracy and superior colour reproduction with 180 degree viewing.

# **CMND** and Control



Run your display network over a local (LAN) connection. CMND and Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

### **Energy saving**

Energy-saving automatic backlight control

### FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs, ensuring that content keeps playing even if the primary source goes down. Simply set a list of alternative inputs to be sure your business is always on.

#### **SmartPower**



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

#### **Place in landscape**

Place in landscape or portrait orientation

#### **SmartPlayer**



Turn your USB into a true cost-effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on-screen menu, and enjoy your own playlists anytime, anywhere.

# **Optional OPS Slot**

Open Pluggable Specification is an industrystandard slot into which you can add an OPScompatible media player. This gives you the ability to upgrade or change your hardware whenever you need to. Turning your display into an all-in-one digital signage solution has become simplicity itself.











# Specifications

#### Connectivity

- Audio output: 3.5 mm jack
- Video input: Display Port1.2 (x 1), DVI-I (x 1), HDMI 2.0 (x 2), USB 2.0 (x 2)
- Audio input: 3.5 mm jack
- Audio input: 3.5 mm jack
- Other connections: OPS
  Video output: DisplayPort 1.2 (x 1), HDMI 2.0
- (x 1) • External control: IR (in/out) 3.5 mm jack, R]45,
- External control: IR (in/out) 3.5 mm jack, RJ45, RS232C (in/out) 2.5 mm jack

#### **Picture/Display**

- Diagonal screen size (metric): 108.0 cm
- Diagonal screen size (inch): 42.5 inch
- Aspect ratio: 16:9
- Panel resolution: 3840 x 2160
- Pixel pitch: 0.2451 x 0.2451 mm
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 500 cd/m<sup>2</sup>
- Display colours: 1.07 Billion
- Contrast ratio (typical): 1200:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Viewing angle (horizontal): 178 degree
- Viewing angle (vertical): 178 degree
- Panel technology: ADS
- Haze: 25%

# Convenience

- Placement: Landscape (24/7), Portrait (24/7)
- · Screen-saving functions: Pixel Shift, Low Bright
- Keyboard control: Hidden, Lockable
- Signal loop through: DisplayPort, RS232, HDMI, IR Loop through
- Energy-saving functions: Smart Power
  Network controllable: RS232, RJ45

#### ~ .

Sound • Built-in speakers: 2 x 10 W RMS

### Power

- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- Consumption (Typical): 62 W
- Consumption (Max): 170 W
- Standby power consumption: 0.5 W
- Energy Label Class: G

#### Supported Display Resolution

 Computer formats: 640 × 480, 60 Hz, 800 × 600, 60 Hz, 1024 × 768, 60 Hz, 1280 × 720, 60 Hz, 1280 × 1024, 60 Hz, 1440 × 900, 60 Hz, 1600 × 900, 60 Hz, 1680 × 1050, 60 Hz, 1920 × 1080, 60 Hz,

- 3840 x 2160, 30, 60 Hz
- Video formats: 480i, 60 Hz, 480p, 60 Hz, 576p, 50 Hz, 576i, 50 Hz, 720p, 50,60 Hz, 1080i, 50, 60 Hz, 1080p, 50, 60 Hz, 2160p, 24, 30, 60 Hz

#### Dimensions

- Set Width: 973.0 mm
- Product weight: 10.71 kg
- Set Height: 561.2 mm
- Set Depth: 63.5 mm
- Set Width (inch): 38.31 inch
- Set Height (inch): 22.09 inch
- Wall Mount: 200 (H) x 200 (V) mm, M6
- Set Depth (inch): 2.50 inch
- Bezel width: 13.9 mm (Even bezel)
- Product weight (lb): 23.61 lb

#### **Operating conditions**

- Altitude: 0 ~ 3000 m
- Temperature range (operation): 0 ~ 40 °C
- MTBF: 50,000 hour(s)
- Temperature range (storage): -20 ~ 60 °C
- Humidity range (operation)[RH]: 20–80% RH (No condensation)
- Humidity range (storage) [RH]: 5–95% RH (No condensation)

#### **Multimedia Applications**

- USB Playback Video: H.263, H.264, H.265, MPEG
- USB Playback Picture: BMP, JPEG, PNG
- USB Playback Audio: AAC, MPEG, HEAAC

#### Accessories

- Included Accessories: AC Switch Cover, Philips logo (x 1), RS232 daisy-chain cable, AC power cord, IR sensor cable (1.8 m) (x 1), Quick start guide (x 1), Remote control and AAA batteries, RS232 cable, USB Cover and screw x 1, Wire Clamper (x 3)
- Stand: BM05922(Optional)

#### **Miscellaneous**

- On-Screen Display Languages: Arabic, Dutch, Danish, English, French, Finnish, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Simplified Chinese, Turkish, Traditional Chinese
- Warranty: 3 year warranty
- Regulatory approvals: CE, FCC, Class A, CCC, RoHS, CB, BSMI, EMF, VCCI, PSB, ETL, CECP, EAC, EnergyStar 8.0



 Issue date 2024-03-31
 © 2024 Koninklijke Philips N.V.

 All Rights reserved.

 Version: 2.0.1
 Specifications are subject to change without notice.

 Trademarks are the property of Koninklijke Philips N.V.

 or their respective owners.

# 43BDL4511D/00