Overview

HP Presentation Barcode Scanner



Model

HP Presentation Barcode Scanner

Part Number: QY439AA

Introduction

The HP Presentation Barcode Scanner is a sleek POS solution that features a user-friendly design, small footprint, and efficient capture of a wide range of 1D and 2D barcodes, including barcodes presented on mobile devices, all at a competitive price point. This all-new general purpose on-counter presentation scanner can be mounted to most surfaces and delivers automatic movement recognition and hand-free operation.

Key Features and Benefits

- Reads most common1D and 2D barcodes, PDF codes and GS1 DataBar for a range of flexible uses.
- Omni-directional operation allows symbol or image capture regardless of the orientation of the scanner for quicker reading.
- Enhanced motion tolerance and technology allow quick reading of barcodes from mobile devices.
- Intuitive feedback following a successful read indicated by a sound and shown by a visual green light shown on the device.
- Scanner is able to read poorly printed or damaged barcodes successfully for quicker checkout.
- Fixed mounting plate allows the scanner to be mounted to most surfaces to help decrease the likelihood of being dropped or knocked over a counter.

Compatibility

The HP Presentation Barcode Scanner is compatible with HP Retail Point of Sale Systems.

NOTE: Not all Point of Sale system models are available in all regions.

Service and Support

Your HP Peripheral Limited Warranty is a three (3) year (HP Option Limited Warranty Period) parts replacement warranty.



Technical Specifications

General

Scanner type

Light source

Nominal working distance

lmager

LEDs

Depth of Field

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

1D Linear Codes

- 5 mils: 0 to 2.5 cm / 0 to 1.0 in
- 7.5 mils: 0 to 8.2 cm / 0 to 3.25 in
- 10 mils: 0 to 12.7 cm / 0 to 5.0 in
- 13 mils UPC: 0 to 15.2 cm / 0 to 6.0 in

2D Linear Codes

+ 0-360°

± 60

± 60°

- 6.6 mils PDF: 3.8 to 7.6 cm / 0 to 3.0 in
- 10 mils Data Matrix: 0.64 to 3.1 cm / 0.25 to 1.25 in
- 10 mils PDF: 0 to 12.7 cm / 0 to 5.0 in
- 15 mils PDF: 0 to 15.2 cm / 0.0 to 6.0 in
- 24 mils Data Matrix: 0 to 12.7 cm / 0 to 5.0 in

25% minimum reflectance

Roll (tilt)

Print contrast

Pitch

Skew

1D/2D decode

symbologies

Factory Default Barcodes* CODE 39 CODE 93 CODE 128 DataMatrix EAN-8 EAN-13 GS1 DataBar Expanded GS1 Databar Omni-directional PDF417 UPC-A UPC-E

*HP factory setting has these code selections enabled by default.



Technical Specifications

Mechanical	
Dimensions (W \times D \times H)	3 x 6 x 4 in (.76 x 1.52 x 1.01 cm)
Weight	Approximately 10 ounces (295 g)
Cable length	6.5 ft (1.9 m)
Color	Black
Interface/Connection Cable	USB
Temperature	
Operating	32 to 104 °F (0 to 40 °C)
Storage/transport	-40 to 158 °F (-40 to 70 °C)
Humidity (non-condensing)	5 - 95%
Power	
Voltage & current	Input Current at 5V = <350 mA (max)

Drivers

Windows UBB HID-KB and OPOS & JPOS (via USB-COM mode drivers)

Operating System

Compatible with:	Genuine Windows Vista [®] Business 32
	Genuine Windows XP Professional
	Genuine Windows Embedded for Point of Service (WEPOS)
	Genuine Windows Embedded POSReady 2009
	Genuine Windows Embedded POSReady 7 32 bit
	Genuine Windows Embedded POSReady 7 64 bit
	Genuine Windows 7 Business 32
	Genuine Windows 7 Business 64

Idle Current at $5V = \langle 250 \text{ mA} (\text{max}) \rangle$

Agency Certifications

C-Tick, VCCI, CSA, CE, FCC



Technical Specifications

Option Kit Contents

HP Presentation Barcode Scanner, USB Cable, HP Point of Sale System Software and Documentation CD.

© Copyright 2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

