

Overview

Models

HP MSM31x/MSM32x Power Supply

J9405B

Product overview

This AC Power Supply is for use with the following Access Points MSM31x, MSM32x and M110. It is also used with the M111 Client Bridge.

Features and benefits

Mobility

- **Multiple power options:** allows the use of a power adapter when PoE is inconvenient

Warranty and support

- **Warranty:** lifetime warranty for as long as you own the product with next-business-day advance replacement (available in most countries), with the exception of the hard disk, which has a 5-year warranty



Technical Specifications

HP MSM31x/MSM32x Power Supply (J9405B)

Physical characteristics	Dimensions	3.7(d) x 1.5(w) x 1.18(h) in. (9.4 x 3.8 x 3 cm)
	Weight	0.88 lb. (0.4 kg)
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 95%, noncondensing
	Nonoperating/Storage temperature	-4°F to 176°F (-20°C to 80°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
Electrical characteristics	Voltage	100-240 VAC
	Current	0.5/0.3 A
	Frequency	50/60 Hz
	Notes	Output voltage: 5 VDC
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

To learn more, visit: www.hp.com/networking

© Copyright 2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

