QuickSpecs

Overview

Models

HP 10GbE al Switch Interconnect Kit

J9165A



QuickSpecs

Technical Specifications

Physical characteristics	Dimensions	4.11(d) x 4.18(w) x 1.4(h) in. (10.44 x 10.62 x 3.56 cm)
Two 1-port CX4 modules	Weight	0.31 lb. (0.14 kg)
Environment	Operating temperature	32°F to 122°F (0°C to 50°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 95% @ 149°F (65°C), noncondensing
Notes	HP 10 GbE al Switch Interconnect Kit includes two 1-port 10-GbE CX4 compatible Interconnect modules for short-distance connectivity using the 0.5 m CX4 cable provided. The ports support a maximum distance of 3m over standard CX4 cables.	
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
	Environment Notes	Weight Environment Operating temperature Operating relative humidity Nonoperating/Storage temperature Nonoperating/Storage relative humidity Notes HP 10 GbE al Switch Inter compatible Interconnect m 0.5 m CX4 cable provided over standard CX4 cables. Services Refer to the HP website at the service-level descriptio services and response time

Cables

HP BladeSystem c-Class .5m 10-GbE CX4 Cable Option	444477-B21
HP BladeSystem c-Class 1m 10-GbE CX4 Cable Option	444477-B22
HP BladeSystem c-Class 3m 10-GbE CX4 Cable Option	444477-B23

To learn more, visit www.hp.com/networking

© Copyright 2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

